




ROMEX NORTH AMERICA
 260 RIVERSIDE DRIVE
 NORTH VANCOUVER, BC V7H 2M2
 PHONE: (604) 913-1579
 www.romexcanada.com



SECTION VIEW

ROMEX® - ADHESION ELUTRIANT (OPTIONAL):

MIXING: TO ACHIEVE A CONSISTENCY THAT IS PLASTIC AND CAN BE SPREAD, POUR 8.5 LITRES OF COOL, CLEAN WATER INTO A CONTAINER. THEN ADD 25KG OF ROMEX® - ADHESION ELUTRIANT AND STIR FOR 3 MINUTES. AFTER 3 MINUTES OF MATURING TIME STIR THROUGH AGAIN BRIEFLY. ALWAYS USE THE ENTIRE CONTAINER.

APPLICATION: APPLIED TO THE SLAB UNDERSIDE WITH A LAYER THICKNESS OF APPROX. 3-5MM OR DIP THE SLAB 2-3CM DEEP INTO THE TUB OF ROMEX® - ADHESION ELUTRIANT.

STORAGE LIFE: 6 MONTHS OF STORAGE LIFE (DRY IN ORIGINAL, SEALED SACK).

ROMEX® - JOINTING MORTAR


PREPARATION: CLEAN OUT JOINTS TO A DEPTH OF AT LEAST 30MM (MINIMUM JOINT WIDTH 5MM). THE SURFACE TO BE JOINTED SHOULD BE CLEANED OUT OF ALL KINDS OF DIRT. ANY ADJOINING SURFACES THAT ARE NOT TO BE JOINTED SHOULD BE TAPED OFF.

STORAGE LIFE: 12-24 MONTHS

*PLEASE SEE MANUFACTURER'S PRODUCT DATA SHEET FOR COMPLETE INFORMATION (VARIES BETWEEN JOINTING MORTAR).

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5315-005



ROMEX® JOINTING MORTAR

WITH OPTIONAL ADHESION ELUTRIANT ON GRADE - PEDESTRIAN (UNBOUND)